

1500 & 1600 Series



Discover The Difference With The New 1500 And 1600 Series Strikes

The HES 1500 and 1600 Series Electric Strikes set a new standard in the industry by offering dynamic integrated adjustability and field configurable options compatible with any cylindrical or mortise lock. The modular design of the platform makes stocking and installing easier with interchangeable faceplates and accessories. For the first time, the aesthetics of an electric strike are complimentary to other surrounding door hardware and blend in with the opening due to the fully finished design available in seven finishes.

Elegant Form And Function

- Adjustable integrated shim for changing door conditions
- Field upgradeable options
- Integrated monitoring of latchbolt and and/or door position switch

Designed With The Installer In Mind

- Accommodates all brands of mortise and cylindrical locks
- Dual voltage 12/24VDC
- Field selectable fail safe/fail secure

Convenient And Versatile

- Interchangeable accessories work with both models
- Field serviceable components
- All faceplates are interchangeable between the 1500 and 1600



Field adjustable integrated shim

Shim will adjust out 1/8"



Dual lock monitoring

The most advanced, modular electric strikes that work with every brand of cylindrical or mortise locks designed to work with a 4-7/8" strike plate.

Visit us on-line at www.imlss.com or ask an IML Representative for more product details.

arizona - california - colorado - nevada - utah - washington



1500 & 1600 Series



Specifications

Certifications

- UL 10C fire-rated, 3 hour single door (fail secure only)
- UL 10C fire-rated, 1-1/2 hour double door
- CAN4-S104 (ULC-S104) fire door conformant
- ANSI/SDI 250.13 windstorm resistant
- ANSI-ASTM E330
- Florida Building Code approved TAS 201, 202, 203
- UL 1034 burglary-resistant listed
- Suitable for outdoor use
- UL 294 (6th Edition) listed
- ANSI/BHMA A156.31, Grade 1
- California Fire Marshal listed
- NFPA-252 fire door compliant
- ASTM-E152 fire door compliant
- PoE friendly
- RoHS compliant

Optional Features

- LM » Lock monitor
- DLM » Dual lock monitors
- LMS » Lock monitor and strike monitor
- DLMS » Dual lock monitors and strike monitor

Standard Features

- Stainless steel construction
- Tamper-resistant
- Dual voltage 12/24 VDC continuous duty
- Static strength 1,500 lbs
- Dynamic strength 70 ft-lbs
- Endurance 1,000,000 cycles
- Field selectable fail safe/fail secure
- Non-handed
- Interchangeable faceplates
- Field replaceable springs and actuator
- Fully finished faceplate, keeper, case, trim
- Field adjustable integrated shim
- ElectroLynx® connectors

Finishes

- 605 » Bright brass
- 606 » Satin brass
- 612 » Satin bronze
- 613E » Dark oxidized satin bronze
- 629 » Bright stainless steel
- 630 » Satin stainless steel
- BLK » Black suede

Visit us on-line at www.imlss.com or ask an IML Representative for more product details.

arizona - california - colorado - nevada - utah - washington

