



SCECTE-MT11-485
SCECTE-MT15-485



CTE Single Door Controller With Multi-technology Reader

The CTE is an ENGAGE enabled single opening controller that allows perimeter and common area openings to be managed in a single system along with Schlage Control smart deadbolts, NDE cylindrical and LE mortise wireless locks. It is ideal for multi-family, commercial mixed use, and retail store front applications.

The CTE is designed to work with a Schlage Multi-Technology credential reader and interface with an electrified lock, electromagnetic lock, electric strike, automatic operator, or exit device to control an opening.

The CTE single door controller is designed for flexibility and can be managed with ENGAGE web and mobile apps or with one of our Software Alliance Member systems.

Features

- Electronics bring more visibility and control to the opening
- Allows an up to 5,000 users with audit trail of up to 2,000 events
- Inputs include door position (DPS), request to exit (REX), request to enter (REN) and remote release (REL)
- Manage users and assign access privileges from virtually anywhere
- Send updates wirelessly at the CTE with the ENGAGE™ mobile application on a Bluetooth® enabled smart phone or tablet. Or leverage the existing Wi-Fi network or built-in No-Tour capability to send periodic updates without visiting the lock.
- Supports holidays and time zones to enable auto lock and unlock during specified periods
- Works with most proximity or high security Schlage smart credentials
- Compatible with Schlage MT11-485 and MT15-485 readers

Visit us on-line at www.imlss.com or ask an IML Representative for more product details.

arizona - california - colorado - nevada - utah - washington

